



**HITEC®** Gamma aerovaporatori con distributore Venturi.

**BENEFIT®** Gamma aerovaporatori con distributore brevettato **LU-VE** Contardo **JET-O-MATIC®**.

**HITEC®** Unit coolers range with Venturi

distributor.

**BENEFIT®** Unit coolers range with patented **JET-O-MATIC®** distributor **LU-VE** Contardo.



## 1450 - 9400 W

Modello	Type	F27HC-F27JC (4 = 4.5 mm)	25-4	36-4	49-4	71-4	107-4	142-4
Potenza	Rating	TC $\Delta T1$ 2,5 °C / 10K	W	1850	2350	3850	4750	9400
Portata d'aria	Air quantity		m <sup>3</sup> /h	900	900	1800	1800	3600
Freccia d'aria	Air throw		m	10,5	10,5	12,5	12,5	15,5
Modello	Type	F27HC-F27JC (6 = 6.0 mm)	19-6	28-6	38-6	55-6	85-6	110-6
Potenza	Rating	TC $\Delta T1$ 2,5 °C / 10K	W	1600	2050	3300	4150	8300
Portata d'aria	Air quantity		m <sup>3</sup> /h	950	950	1900	1900	3800
Freccia d'aria	Air throw		m	11,0	11,0	13,0	13,0	16,0
Modello	Type	F27HC-F27JC (7 = 7.0 mm)	16-7	23-7	31-7	46-7	70-7	92-7
Potenza	Rating	TC $\Delta T1$ 2,5 °C / 10K	W	1450	1850	3000	3700	7600
Portata d'aria	Air quantity		m <sup>3</sup> /h	1000	1000	2000	2000	4000
Freccia d'aria	Air throw		m	11,5	11,5	13,5	13,5	17,0

### DATI COMUNI / COMMON DATA

Elettroventilatori	Fans	$\varnothing$ 275 mm	n°	1	1	2	2	3	4
			W	85	85	170	170	255	340
Assorb. motori	Motor power consumption	1-230V 50Hz	A	0,6	0,6	1,2	1,2	1,8	2,4
Sbrinamento	Defrost	E 230 V	W	1220	1220	2160	2160	3080	4000
Vol. circuito	Circuit volume		dm <sup>3</sup>	0,8	1,3	1,6	2,3	3,3	4,3
Dimensioni	Dimensions	A	mm	678	678	1048	1048	1418	1788

