



HITEC® Gamma aerovaporatori con distributore Venturi.

HITEC® Unit coolers range with Venturi distributor.

BENEFIT® Gamma aerovaporatori con distributore brevettato **LU-VE** Contardo **JET-O-MATIC®**.

BENEFIT® Unit coolers range with patented **JET-O-MATIC®** distributor **LU-VE** Contardo.



4000 - 27500 W

Modello	Type	F35HC-F35JC (4 = 4.5 mm)	73-4	106-4	145-4	215-4	272-4	323-4	362-4	430-4
Potenza	Rating	TC $\frac{2,5}{\Delta T1}$ °C 10K	W	5400	6800	10900	13600	18700	20400	27500
Portata d'aria	Air quantity		m³/h	2600	2400	5200	4800	7450	7200	9600
Freccia d'aria	Air throw		m	19,5	18,0	23,0	22,0	26,0	25,0	29,0
Modello	Type	F35HC-F35JC (6 = 6.0 mm)	59-6	84-6	117-6	174-6	218-6	261-6	290-6	348-6
Potenza	Rating	TC $\frac{2,5}{\Delta T1}$ °C 10K	W	4500	5900	9200	12000	16100	18000	24000
Portata d'aria	Air quantity		m³/h	2650	2500	5300	5000	7700	7500	10300
Freccia d'aria	Air throw		m	20,0	18,5	23,5	22,5	26,5	25,5	29,5
Modello	Type	F35HC-F35JC (7 = 7.0 mm)	47-7	69-7	94-7	143-7	179-7	213-7	238-7	284-7
Potenza	Rating	TC $\frac{2,5}{\Delta T1}$ °C 10K	W	4000	5400	8200	11000	14600	16500	22000
Portata d'aria	Air quantity		m³/h	2700	2600	5400	5200	7950	7800	10600
Freccia d'aria	Air throw		m	20,5	19,0	24,0	23,0	27,0	26,0	31,0

DATI COMUNI / COMMON DATA

Elettroventilatori	Fans	Ø 350 mm	n°	1	1	2	2	3	3	4	4
			W	175	175	350	350	525	525	700	700
Assorb. motori	Motor power consumption	1-230V 50-hz	A	0,8	0,8	1,6	1,6	2,4	2,4	3,2	3,2
Sbrinamento	Defrost	E 230 V	W	2075	2975	3680	5280	7620	7620	9940	9940
Vol. circuito	Circuit volume		dm³	2,1	3,2	4,0	6,0	7,4	8,7	9,7	11,5
Dimensioni	Dimensions	A	mm	865	865	1420	1420	1975	1975	1530	2530

